

# Inhaltsverzeichnis

- Links** ..... 3
- using realm** ..... 3
  - sssd.conf ..... 3



# AD Domain Join

Joinin Linux to an AD Domain.



dieses Thema ist noch in Arbeit!

## Links

Weiterführende Links zum Thema:

- [https://access.redhat.com/documentation/en-us/red\\_hat\\_enterprise\\_linux/7/html/windows\\_integration\\_guide/sss-integration-intro#sss-posix](https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/7/html/windows_integration_guide/sss-integration-intro#sss-posix)
- [https://staff.washington.edu/ketcham/sss-uwwi-integration/uwwi\\_group\\_problems/sss-problem-with-unix-ids.html](https://staff.washington.edu/ketcham/sss-uwwi-integration/uwwi_group_problems/sss-problem-with-unix-ids.html)

## using realm

Auf neueren Linuxvarianten geht der Domain Join ganz einfach über das realm toolset.

```
# realm join aendy.ch --automatic-id-mapping=no
```

## sss.conf

Miminalistic conf, but users without domainpart i.e. username instead of username@domain and with UID/GID from Active Directory Property.

[sss.conf](#)

```
[sss]
domains = aendy.ch
config_file_version = 2
services = nss, pam

[domain/aendy.ch]
default_shell = /bin/bash
krb5_store_password_if_offline = True
cache_credentials = True
krb5_realm = AENDY.CH
realmd_tags = manages-system joined-with-adcli
id_provider = ad
fallback_homedir = /home/%u
```

```
ad_domain = aendy.ch  
use_fully_qualified_names = false  
ldap_id_mapping = False  
access_provider = ad
```

From:

<https://aha-it.ch/wiki/> - **AHa-IT**

Permanent link:

<https://aha-it.ch/wiki/lx/ad-domain?rev=1667664246>

Last update: **05.11.2022 16:04**

